

PIPE SIZE	O.D. INCHES	5	10S	10	20	30	STD	40	60	XH	80	100	120	140	160	XXH
1/8	0.405	0.035	0.049	0.049			0.068	0.068		0.095	0.095					
		0.1383	0.1863	0.1863			0.2447	0.2447		0.3145	0.3145					
1/4	0.540	0.049	0.065	0.065			0.088	0.088		0.119	0.119					
		.2570	0.3297	0.3297			0.4248	0.4248		0.5351	0.5351					
3/8	0.675	0.049	0.065	0.065			0.091	0.091		0.126	0.126					
		0.3276	0.4235	0.4235			0.5675	0.5675		0.7388	0.7388					
1/2	0.840	0.065	0.083	0.083			0.109	0.109		0.147	0.147				0.187	0.294
		0.5383	.6710	.6710			.8510	.8510		1.088	1.088				1.304	1.714
3/4	1.050	0.065	0.083	0.083			0.113	0.113		0.154	0.154				0.218	0.308
		0.6838	0.8572	0.8572			1.131	1.131		1.474	1.474				1.937	2.441
1	1.315	0.065	0.109	0.109			0.133	0.133		0.179	0.179				.250	0.358
		0.8678	1.404	1.404			1.679	1.679		2.172	2.172				2.844	3.659
1 ¼	1.660	0.065	0.109	0.109			0.140	0.140		0.191	0.191				.250	0.382
		1.107	1.806	1.806			2.273	2.273		2.997	2.997				3.765	5.214
1 ½	1.900	0.065	0.109	0.109			0.145	0.145		.200	.200				0.281	.400
		1.274	2.085	2.085			2.718	2.718		3.631	3.631				4.859	6.408
2	2.375	0.065	0.109	0.109			0.154	0.154		0.218	0.218				0.343	0.436
		1.604	2.638	2.638			3.653	3.653		5.022	5.022				7.444	9.029
2 ½	2.875	0.083	.120	.120			0.203	0.203		0.276	0.276				0.375	0.552
		2.475	3.531	3.531			5.793	5.793		7.661	7.661				10.01	13.70
3	3.500	0.083	.120	.120			0.216	0.216		.300	.300				0.437	.600
		3.029	4.332	4.332			7.576	7.576		10.25	10.25				14.32	18.58
3 ½	4.000	0.083	.120	.120			0.226	0.226		0.318	0.318					0.636
		3.472	4.937	4.937			9.109	9.109		12.51	12.51					22.85
4	4.500	0.083	.120	.120			0.237	0.237	0.281	0.337	0.337		0.437		0.531	0.674
		3.915	5.613	5.613			10.79	10.79	12.66	14.98	14.98		19.01		22.51	27.54
5	5.563	0.109	0.134	0.314			0.258	0.258		0.375	0.375		.500		0.625	.750
		6.349	7.770	7.770			14.62	14.62		20.78	20.78		27.04		32.96	38.55
6	6.625	0.109	0.134	0.134			.280	.280		0.432	0.432		0.562		0.718	0.864
		7.585	9.289	9.289			18.97	18.97		28.57	28.57		36.39		45.30	53.16
8	8.625	0.109	0.148	0.148	.250	0.277	0.322	0.322	0.406	.500	.500	0.593	0.718	0.812	0.906	0.875
		9.914	13.40	13.40	22.36	24.70	28.55	28.55	35.64	43.39	43.39	50.87	60.63	67.76	74.69	72.42
9	9.625						0.342			.500						
							33.90			48.72						
10	10.750	0.134	0.165	0.165	.250	0.307	0.365	0.365	.500	.500	0.593	0.718	0.843	1.000	1.125	
		15.19	18.65	18.65	28.04	34.24	40.48	40.48	54.74	54.74	64.33	76.93	89.20	104.0	115.7	
12	12.750	0.165	.180	.180	.250	.330	0.375	0.406	0.562	.500	0.688	0.843	1.000	1.125	1.312	
		22.18	24.16	24.20	33.38	43.77	49.56	53.33	73.16	65.42	88.51	107.2	125.5	139.7	160.3	
14	14.000		0.188	.250	.250	0.375	0.375	0.438	0.593	.500	.750	0.937	1.093	1.250	1.406	
			27.73	36.71	45.68	54.57	54.57	63.37	84.91	72.09	106.1	130.7	150.7	170.2	189.1	
16	16.000		0.188	.250	0.312	0.375	0.375	.500	0.656	.500	0.844	1.031	1.218	1.437	1.593	
			31.75	42.05	52.36	62.58	62.58	82.77	107.5	82.77	136.5	164.8	192.3	223.5	245.1	
18	18.000		0.188	.250	0.312	0.437	0.375	0.562	.750	.500	0.937	1.156	1.375	1.562	1.781	
			35.76	47.39	59.03	82.06	70.59	104.8	138.2	93.45	170.8	208.0	244.1	274.2	308.5	
20	20.000		0.218	.250	0.375	.500	0.375	0.593	0.812	.500	1.031	1.280	1.500	1.750	1.968	
			46.05	52.73	78.60	140.1	78.60	122.9	166.4	104.1	208.9	256.1	296.4	341.1	379.0	
22	22.000			.250	0.375	.500	0.375		0.875	.500	1.125	1.375	1.625	1.875	2.125	
				58.07	86.61	114.8	86.61		197.4	114.8	250.8	277.0	353.6	403.0	451.1	
24	24.000		.250	.250	0.375	0.562	0.375	0.687	0.968	.500	1.218	1.531	1.812	2.062	2.343	
			63.41	63.41	94.62	140.8	94.62	171.2	238.1	125.5	296.4	367.4	429.4	483.1	541.9	
26	26.000			0.312	.500		0.375			.500						
				85.60	136.2		102.6			136.2						
28	28.000			0.312	.500	0.625	0.375			.500						
				92.26	146.8	182.7	110.6			146.8						
30	30.000		0.312	0.312	.500	0.625	0.375			.500						
			98.93	98.93	157.5	196.1	118.6			157.5						
32	32.000			0.312	.500	0.625	0.375	0.688		.500						
				105.6	168.2	209.4	126.7	230.1		168.2						
34	34.000			0.344	.500	0.625	0.375	0.688		.500						
				123.7	178.9	222.8	134.7	244.8		178.9						
36	36.000			0.312	.500	0.625	0.375	.750		.500						
				118.9	189.60	236.1	142.7	282.3		189.6						
42	42.000						0.375			.500						
							166.7			221.6						
48	48.000						0.375			.500						
							190.7			253.6						

Gray Shading: Wall Thickness in inches White Shading: Weight per foot in lbs.

	PIPE	BUTTWELD FITTINGS	PRESSURE FITTINGS	FLANGES	PIPE NIPPLES
TYPES	Seamless Welded X-Ray	Elbow, Tee, Reducer, Cap, Stub End, Cross	Elbow, Tee, Coupling, Union, Plug, Cap, Bushing, Insert, Olet	Weld Neck, Slip-On, Blind, Socket Weld, Threaded, Lap Joint	Thread Both End
SIZES	1/4" - 24" Seamless 1/4" - 36" Welded	1/2" - 36"	1/8" - 4"	1/2" - 36"	1/8" - 6"
SCHEDULES	10S - XXH	10S - XXH		10S - XXH	40S / 80S / 160 / XXH
PRESSURES			150# / 3000# / 6000#	150# / 300# / 600# / 900# / 1500# / 2500#	
AVAILABLE GRADES					
304/304L	✓	✓	✓	✓	✓
316/316L	✓	✓	✓	✓	✓
304H	✓	★	★	★	★
DUPLEX 2205	✓	✓	✓	✓	★
NICKEL 200/201	✓	✓	✓	✓	★
ALLOY 20	✓	✓	✓	✓	★
ALLOY C276	✓	✓	✓	✓	★
ALLOY 400	✓	✓	✓	✓	★
ALLOY 600	✓	✓	★	✓	★
ALLOY 800H/HT	✓	★	★	★	★
SERVICES	24-Hour Emergency Service Pipe Modifications: Cut to Specified Length, Beveling, Threading, Grooving Flange Modifications: Flat Facing, Adding Ring Type Joint Groove, Straight or Taper Boring, Reducing Slip-Ons Fitting Modifications: Taper Boring to Specified Thickness, Formed Return Bends, Stub End Modification Project Specific Requirements: Color Coding and Tagging, Flange Protectors and Pipe Caps, Packaging/Crating Material Testing: X-Ray, Positive Material Identification (PMI), Non-Destructive Testing (NDT) Expedited Transportation: Air Freight, Dedicated Truck Lanes, Hot Shot Delivery Service				

✓ indicates Stocking Grade ★ indicates Made to Order

ABOUT US

Stainless & Nickel Alloy Piping Products was established in 2016 by an experienced team of PVF industry veterans with the belief in providing customers quick, dependable service and an extensive inventory of stainless steel and nickel alloy pipe, fittings, and flanges. We are headquartered just outside Houston, TX with multiple locations strategically positioned to quickly reach the entire continental United States.

We understand the dynamics of the industry and the personal service required to overcome its challenges. SNAPP offers familiar faces and years of experience with a new take on master distribution of stainless steel and nickel alloy products.

To stand behind our **"Best in Service"** strategy, we developed a team that takes pride in their company, provide an extensive product line with immediately-available inventory, built unwavering partnerships with our suppliers, established unmatched quote response times, and process all shipments with speed and accuracy that is unrivaled in the business.

LOCATIONS

CORPORATE HEADQUARTERS:

Pearland, TX 832-617-8200

DISTRIBUTION CENTER:

La Porte, TX 281-800-9610

BRANCH LOCATIONS:

Salt Lake City, UT	385-430-1990
St. Louis, MO	314-391-2500
Charlotte, NC	980-265-4800
Cincinnati, OH	513-964-5710

